

## Compressed Sheet Packing Aramid Fibers/NBR Binder

STYLE 1125

### Construction/Description

#### Compressed Aramid Fiber Style 1125

Style 1125 is a compressed aramid fiber sheet gasket material produced by a combination of aramid and other synthetic fibers and bonded with Nitrile rubber (NBR). It is manufactured through the hot calender process under rigorous quality control standards that are registered under ISO-9002 certification.

### Application/Service

Style 1125 is a very good general service gasket material that has numerous applications in the process industries and in the water and waste water industry. It is also commonly used in equipment such as valves and pumps. Style 1125 is suitable for service handling the following general media categories:

- » Mild Inorganic Acids
- » Mild Organic Acids
- » Concentrated Alkalies
- » Diluted Alkalies
- » Water
- » Brine
- » Air
- » Industrial Gases
- » Animal Oils
- » Synthetic Oils
- » Vegetable Oils
- » Petroleum and Derivatives
- » General Chemicals
- » Aliphatic Solvents
- » Aromatic Solvents
- » Oxygenated Solvents
- » Neutral Solutions
- » Refrigerants

*Style 1125 is not suitable for most steam applications*

### Product Data

Temperature Limits		Pressure Limits	ASTM Line Call Out	Color
Minimum	Limited Maximum			
-45°F 40°C	750°F 400°C	Vacuum to 1370 PSI (95 bar)	ASTM F104-F712111-B5E11M5	Green

#### *Service is Our Business*

For "Typical Physical Properties", PxT limits and Sealability Curve, please contact the Sales Department. Technical properties are typical and are presented in good faith, but no warranty is expressed or implied.

All technical advise and recommendation are rendered by Seller free of charge. While based on data believed to be reliable, seller assumes no responsibility.