

Gasket Dimensions for XR-RJ (RTJ)

150#			
NPS Nominal Pipe Size	150#		
	Gasket I.D.	Gasket O.D.	Guide Ring O.D.
1/2"	-	-	-
3/4"	-	-	-
1"	1-1/8"	1-5/8"	2-5/8"
1 1/4"	1-3/8"	1-7/8"	3"
1 1/2"	1-5/8"	2-1/4"	3-3/8"
2"	2-1/8"	2-7/8"	4-1/8"
2 1/2"	2-3/4"	3-5/16"	4-7/8"
3"	3-5/16"	3-15/16"	5-3/8"
4"	4-5/16"	5-3/16"	6-7/8"
5"	5-5/16"	6-3/16"	7-3/4"
6"	6-5/16"	7-3/16"	8-3/4"
8"	8-1/4"	9-3/16"	11"
10"	10-5/16"	11-7/16"	13-3/8"
12"	12-3/16"	13-9/16"	16-1/8"
14"	13-7/16"	14-15/16"	17-3/4"
16"	15-5/16"	16-15/16"	20-1/4"
18"	17-1/4"	19"	21-5/8"
20"	19-1/8"	21-1/8"	23-7/8"
24"	23"	25-1/4"	28-1/4"

Style XR-RJ is a replacement gasket for solid metal oval or octagonal API Ring Joint gasket.

These gaskets may be used as a replacement when spiral wound gaskets are preferred or when the gasket groove is badly worn, thereby saving the cost of flange replacement.

NOTE: O.D. Dimensions of gaskets are nominal. Actual dimensions are approximately 1/32" less to incur proper assembly in rings.