



## Gasket Dimensions for XR-RJ (RTJ)

900#			
NPS Nominal Pipe Size	900#		
	Gasket I.D.	Gasket O.D.	Guide Ring O.D.
1/2"	9-1/16"	1-1/16"	2-1/2"
3/4"	13/16"	1-3/8"	2-3/4"
1"	1-1/16"	1-5/8"	3-1/8"
1 1/4"	1-5/16"	2"	3-1/2"
1 1/2"	1-9/16"	2-3/8"	3-7/8"
2"	2-1/4"	3-1/4"	5-5/8"
2 1/2"	2-9/16"	3-5/8"	6-1/2"
3"	3-3/16"	4-3/16"	6-5/8"
4"	4-1/16"	5-3/16"	8-1/8"
5"	5-5/16"	6-7/16"	9-3/4"
6"	6-5/16"	7-5/8"	11-3/8"
8"	8-1/4"	9-15/16"	14-1/8"
10"	10-5/16"	12"	17-1/8"
12"	12-7/8"	14-1/4"	19-5/8"
14"	13-13/16"	15-9/16"	20-1/2"
16"	15-9/16"	17-9/16"	22-5/8"
18"	17-11/16"	19-15/16"	25-1/8"
20"	19-11/16"	21-15/16"	27-1/2"
24"	23-3/16"	25-15/16"	33"

Style XR-RJ is a replacement gasket for solid metal oval or octagonal API Ring Joint gasket.

These gaskets may be used as a replacement when spiral wound gaskets are preferred or when the gasket groove is badly worn, thereby saving the cost of flange replacement.

**NOTE:** O.D. Dimensions of gaskets are nominal. Actual dimensions are approximately 1/32" less to incur proper assembly in rings.