



Gasket Dimensions for Full Face Class 300

per MSS-SP44 and C207-55 AWWA

Pipe Size	Gasket O.D.	Bolt Holes		
		No.	Size	B.C. Dia.
1/4"	-	-	-	-
3/8"	-	-	-	-
1/2"	3 - 3/4"	4	5/8"	2 - 5/8"
3/4"	4 - 5/8"	4	3/4"	3 - 1/4"
1"	4 - 7/8"	4	3/4"	3 - 1/2"
1 - 1/4"	5 - 1/4"	4	3/4"	3 - 7/8"
1 - 1/2"	6 - 1/8"	4	7/8"	4 - 1/2"
2"	6 - 1/2"	8	3/4"	5"
2 - 1/2"	7 - 1/2"	8	7/8"	5 - 7/8"
3"	8 - 1/4"	8	7/8"	6 - 5/8"
3 - 1/2"	9"	8	7/8"	7 - 1/4"
4"	10"	8	7/8"	7 - 7/8"
*4 - 1/2"	10 - 1/2"	8	7/8"	8 - 1/2"
5"	11"	8	7/8"	9 - 1/4"
6"	12 - 1/2"	12	7/8"	10 - 5/8"
*7"	14"	12	1"	11 - 7/8"
8"	15"	12	1"	13"
*9"	16 - 1/4"	12	1 - 1/8"	14"
10"	17 - 1/2"	16	1 - 1/8"	15 - 1/4"
12"	20 - 1/2"	16	1 - 1/4"	17 - 3/4"
14"	23"	20	1 - 1/4"	20 - 1/4"
*15"	24 - 1/2"	20	1 - 3/8"	21 - 1/2"
16"	25 - 1/2"	20	1 - 3/8"	22 - 1/2"
18"	28"	24	1 - 3/8"	24 - 3/4"
20"	30 - 1/2"	24	1 - 3/8"	27"
*22"	33"	24	1 - 5/8"	29 - 1/4"
24"	36"	24	1 - 5/8"	32"
*26"	38 - 1/4"	28	1 - 7/8"	34 - 1/2"
*28"	40 - 3/4"	28	1 - 7/8"	37"
30"	43"	28	2"	39 - 1/4"
*32"	45 - 1/4"	28	2 - 1/8"	41 - 1/2"
*34"	47 - 1/2"	32	2 - 1/8"	43 - 1/2"
36"	50"	32	2 - 1/4"	46"
*38"	52 - 1/4"	36	2 - 1/4"	48"
*40"	54 - 1/2"	36	2 - 1/4"	50 - 1/4"



42"	57"	36	2 - 1/4"	52 - 3/4"
*44"	59 - 1/4"	40	2 - 1/4"	55"
*46"	61 - 1/2"	40	2 - 1/4"	57 - 1/4"
48"	65"	-	-	60 - 3/4"

***Sizes marked are not in current flange standards but are still used.**

NOTE: Bolt Holes in Flanges 26" and larger may be specified 1/8" less in diameter

All technical advice and recommendation are rendered by seller free of charge. While based on data believed to be reliable, seller assumes no responsibility.