



## Gasket Dimensions for Full Face Class 600

per MSS-SP44 and C207-55 AWWA

600#					
Pipe Size	Gasket I.D.	Gasket O.D.	Bolt Holes		
			No.	Size	Circle
1/4"	-	3 - 3/8"	4	5/8"	2 - 1/4"
1/2"	27/32"	3 - 3/4"	4	5/8"	2 - 5/8"
3/4"	1 - 1/16"	4 - 5/8"	4	3/4"	3 - 1/4"
1"	1 - 5/16"	4 - 7/8"	4	3/4"	3 - 1/2"
1 - 1/4"	1 - 21/32"	5 - 1/4"	4	3/4"	3 - 7/8"
1 - 1/2"	1 - 29/32"	6 - 1/8"	4	7/8"	4 - 1/2"
2"	2 - 3/8"	6 - 1/2"	8	3/4"	5"
2 - 1/2"	2 - 7/8"	7 - 1/2"	8	7/8"	5 - 7/8"
3"	3 - 1/2"	8 - 1/4"	8	7/8"	6 - 5/8"
3 - 1/2"	4"	9"	8	1"	7 - 1/4"
4"	4 - 1/2"	10 - 3/4"	8	1"	8 - 1/2"
5"	5 - 9/16"	13"	8	1 - 1/8"	10 - 1/2"
6"	6 - 5/8"	14"	12	1 - 1/8"	11 - 1/2"
8"	8 - 5/8"	16 - 1/2"	12	1 - 1/4"	13 - 3/4"
10"	10 - 3/4"	20"	16	1 - 3/8"	17"
12"	12 - 3/4"	22"	20	1 - 3/8"	19 - 1/4"
14"	14"	23 - 3/4"	20	1 - 1/2"	20 - 3/4"
16"	16"	27"	20	1 - 5/8"	23 - 3/4"
18"	18"	29 - 1/4"	20	1 - 3/4"	25 - 3/4"
20"	20"	32"	24	1 - 3/4"	28 - 1/2"
24"	24"	37"	24	2"	33"

All technical advice and recommendation are rendered by seller free of charge. While based on data believed to be reliable, seller assumes no responsibility.