

Red Rubber Premium Grade SBR

STYLE 1110-00

Construction/Description

Red Rubber Premium Grade SBR ASTM D 1330 Grade 1

Non-oil resistance styrene-butadiene rubber mixture together with added compounding materia, vulcanized into a smooth finish with uniform quality and thickness. Suitable for gasketing.

Application/Service

Generally resistant to most moderat chemicals wet or dry organic acids, alcohols, ketones, and aldehydes. It is generally attacked by ozone, strong acides, fats, oils, greases, and most hydrocarbons.

Product Data

Color	Finish	Duro	Tensile	Elongation	Temperature	ASTM Specifications
Red	Smooth	75+/-5	700 PSI	250%	200°F 93°C	D1330 Grade 1

Red Rubber Commercial Grade

STYLE 1110-01

Construction/Description

Red Rubber Commercial Grade

Red Rubber Commercial Grade is a low cost SBR blend, non-oil resistant material. It has good water resistance and is suitable for gasketing.

Application/Service

Generally resistant to most moderate chemicals, and wet or dry organic acids. It is generally attacked by ozone, strong acids, fats, oils, greases, and most hydrocarbons.

Product Data

Color	Finish	Duro	Tensile	Elongation	Temperature
Red	Smooth	65	400 PSI	200%	180°F 83°C

Service is Our Business

All technical advise and recommendation are rendered by Seller free of charge. While based on data believed to be reliable, seller assumes no responsibility.